

SPEC & PRICE LIST

MAVERICK 1705S 21inch NORMAL RIM

[2-piece]

SIZE	Price (JPY/1pc)			S-Lo Disk 5H-114.3 5H-120						Lo Disk 5H-112 5H-114.3 5H-120						Hi Disk 5H-112 5H-114.3 5H-120									
	SBC	HYPER METAL BLACK	GLAZE BLACK	Order Inset	Inset (Rim Depth) mm						Order Inset	Inset (Rim Depth) mm						Order Inset	Inset (Rim Depth) mm						
					50(59)	44(65)	38(71)	32(77)	26(83)			48~17	45(57)	39(63)	33(69)	27(75)	21(81)			32~1			30(56)	24(62)	18(68)
21×9.0J	¥121,000	¥115,000	¥111,000	55~24	50(59)	44(65)	38(71)	32(77)	26(83)		48~17	45(57)	39(63)	33(69)	27(75)	21(81)		32~1			30(56)	24(62)	18(68)	12(74)	6(80)
21×9.5J	¥122,000	¥116,000	¥112,000	55~17	50(65)	44(71)	38(77)	32(83)	26(89)	20(95)	50~10	45(63)	39(69)	33(75)	27(81)	21(87)	15(93)	38~7		36(56)	30(62)	24(68)	18(74)	12(80)	6(86)
21×10.0J	¥123,000	¥117,000	¥113,000	55~18	50(72)	44(78)	38(84)	32(90)	26(96)	20(102)	50~11	45(70)	39(76)	33(82)	27(88)	21(94)	15(100)	45~6	42(57)	36(63)	30(69)	24(75)	18(81)	12(87)	6(93)
21×10.5J	¥124,000	¥118,000	¥114,000	55~24	50(78)	44(84)	38(90)	32(96)	26(102)		50~17	45(76)	39(82)	33(88)	27(94)	21(100)		46~1	42(63)	36(69)	30(75)	24(81)	18(87)	12(93)	6(99)
21×11.0J	¥125,000	¥119,000	¥115,000	55~24	50(84)	44(90)	38(96)	32(102)	26(108)		50~17	45(82)	39(88)	33(94)	27(100)	21(106)		46~1	42(69)	36(75)	30(81)	24(87)	18(93)	12(99)	6(105)

* There is no protrusion of the top surface of the disk from the edge of the rim flange on all sizes.

■ DISK FINISH: SBC, HMB (Hyper Metal Black), Glaze Black

■ COMPONENT PARTS : CENTER CAP (Selectable from 2 types of Hi type and 6 types of Lo type), AIR VALVE

■ RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

※ SAME PRICES ON YOUR CUSTOM ORDER.

※ The bolt hole diameter of all specs of MAVERICK 1705S are ϕ 14.5. Hub collar ring is recommended when using M12 bolts and nuts.

SIZE	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)			
	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi	
21 Normal	—	—	—	—	ϕ 66.5	705KG	ϕ 30	ϕ 14.5	ϕ 73	690KG	ϕ 30	ϕ 14.5	ϕ 72.5	720KG	ϕ 30	ϕ 14.5	33	40	56	
20 Reverse	—	—	—	—																
20 Normal	ϕ 65	540KG	ϕ 30	ϕ 14.5									700KG	—	—	—				—
19 Reverse														—	—	—				—
19 Normal														—	—	—				—
18 Reverse	—	—	—	—																

SPEC & PRICE LIST

MAVERICK 1705S 20inch REVERSE RIM

[2-piece]

SIZE	Price (JPY/1pc)			S-Lo Disk 5H-114.3 5H-120						Lo Disk 5H-112 5H-114.3 5H-120						Hi Disk 5H-112 5H-114.3 5H-120											
	SBC	HYPER METAL BLACK	GLAZE BLACK	Order Inset	Inset (Rim Depth) mm						Order Inset	Inset (Rim Depth) mm						Order Inset	Inset (Rim Depth) mm								
					53(44)	47(50)	41(56)	37(60)				50~30	48(42)	42(48)	36(54)	30(60)				34~14			33(41)	27(47)	21(53)	15(59)	
20×8.0J	(¥107,000)	(¥101,000)	(¥97,000)	55~37	53(44)	47(50)	41(56)	37(60)			50~30	48(42)	42(48)	36(54)	30(60)			34~14			33(41)	27(47)	21(53)	15(59)			
20×8.5J	(¥108,000)	(¥102,000)	(¥98,000)	55~30	53(50)	47(56)	41(62)	35(68)	30(73)		50~23	48(48)	42(54)	36(60)	30(66)	24(72)		40~7			39(41)	33(47)	27(53)	21(59)	15(65)	9(71)	
20×9.0J	(¥109,000)	(¥103,000)	(¥99,000)	55~22	53(56)	47(62)	41(68)	35(74)	29(80)	23(86)	50~15	48(54)	42(60)	36(66)	30(72)	24(78)	18(84)	46~-1			45(41)	39(47)	33(53)	27(59)	21(65)	15(71)	9(77)
20×9.5J	(¥110,000)	(¥104,000)	(¥100,000)	55~22	53(63)	47(69)	41(75)	35(81)	29(87)	23(93)	50~15	48(61)	42(67)	36(73)	30(79)	24(85)	18(91)	46~-1			45(48)	39(54)	33(60)	27(66)	21(72)	15(78)	9(84)
20×10.0J	(¥111,000)	(¥105,000)	(¥101,000)	55~28	53(69)	47(75)	41(81)	35(87)	29(93)		50~21	48(67)	42(73)	36(79)	30(85)	24(91)		46~-5			45(54)	39(60)	33(66)	27(72)	21(78)	15(84)	9(90)
20×10.5J	(¥112,000)	(¥106,000)	(¥102,000)	55~24	53(75)	47(81)	41(87)	35(93)	29(99)		50~17	48(73)	42(79)	36(85)	30(91)	24(97)	18(103)	46~-1			45(60)	39(66)	33(72)	27(78)	21(84)	15(90)	9(96)

NOTE: FOR OUTER RIM DEPTHS OF 44mm OR LESS, THE TOP SURFACE OF THE Disk PROTRUDES FROM THE EDGE OF THE RIM FLANGE.
(When the outer rim depth is 44mm, 1.0mm protrudes.)

■ DISK FINISH: SBC, HMB (Hyper Metal Black), Glaze Black

■ COMPONENT PARTS : CENTER CAP (Selectable from 2 types of Hi type and 6 types of Lo type), AIR VALVE

■ RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

※ SAME PRICES ON YOUR CUSTOM ORDER.

※ The bolt hole diameter of all specs of MAVERICK 1705S are φ14.5. Hub collar ring is recommended when using M12 bolts and nuts.

SIZE	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)								
	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUBφ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi						
21 Normal	—	—	—	—	φ66.5	705KG	φ30	φ14.5	φ73	690KG	φ30	φ14.5	φ72.5	720KG	φ30	φ14.5	33	40	56						
20 Reverse	—	—	—	—																					
20 Normal	φ65	540KG	φ30	φ14.5																					
19 Reverse																				700KG	—	—	—	—	—
19 Normal																									
18 Reverse	—	—	—	—																					

SPEC & PRICE LIST

MAVERICK 1705S 20inch NORMAL RIM

[2-piece]

SIZE	Price (JPY/1pc)			S-Lo Disk 5H-114.3								Lo Disk 5H-100 5H-112 5H-114.3 5H-120								Hi Disk 5H-114.3										
	SBC	HYPER METAL BLACK	GLAZE BLACK	Order Inset	Inset (Rim Depth) mm								Order Inset	Inset (Rim Depth) mm								Order Inset	Inset (Rim Depth) mm							
20×8.5J	¥108,000	¥102,000	¥98,000	46~24		44(59)	38(65)	32(71)	26(77)			39~17		39(57)	33(63)	27(69)	21(75)			23~1				23(56)	17(62)	11(68)	5(74)			
20×9.0J	¥109,000	¥103,000	¥99,000	53~18	50(59)	44(65)	38(71)	32(77)	26(83)	20(89)		46~11	45(57)	39(63)	33(69)	27(75)	21(81)	15(87)		30~5			30(56)	24(62)	18(68)	12(74)	6(80)			
20×9.5J	¥110,000	¥104,000	¥100,000	53~12	50(65)	44(71)	38(77)	32(83)	26(89)	20(95)	14(101)	50~5	45(63)	39(69)	33(75)	27(81)	21(87)	15(93)	9(99)	36~-12			36(56)	30(62)	24(68)	18(74)	12(80)	6(86)		
20×10.0J	¥111,000	¥105,000	¥101,000	53~6	50(72)	44(78)	38(84)	32(90)	26(96)	20(102)	14(108)	50~-1	45(70)	39(76)	33(82)	27(88)	21(94)	15(100)	9(106)	43~-17	42(57)	36(63)	30(69)	24(75)	18(81)	12(87)	6(93)			
20×10.5J	¥112,000	¥106,000	¥102,000	53~12	50(78)	44(84)	38(90)	32(96)	26(102)	20(108)	14(114)	50~5	45(76)	39(82)	33(88)	27(94)	21(100)	15(106)	9(112)	43~-11	42(63)	36(69)	30(75)	24(81)	18(87)	12(93)	6(99)			
20×11.0J	¥113,000	¥107,000	¥103,000	53~12	50(84)	44(90)	38(96)	32(102)	26(108)	20(114)	14(120)	50~5	45(82)	39(88)	33(94)	27(100)	21(106)	15(112)	9(118)	43~-12	42(69)	36(75)	30(81)	24(87)	18(93)	12(99)	6(105)			

* There is no protrusion of the top surface of the disk from the edge of the rim flange on all sizes.

■ DISK FINISH: SBC, HMB (Hyper Metal Black), Glaze Black

■ COMPONENT PARTS : CENTER CAP (Selectable from 2 types of Hi type and 6 types of Lo type), AIR VALVE

■ RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

※ SAME PRICES ON YOUR CUSTOM ORDER.

※ The bolt hole diameter of all specs of MAVERICK 1705S are ϕ 14.5. Hub collar ring is recommended when using M12 bolts and nuts.

SIZE	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)					
	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi			
21 Normal	—	—	—	—	ϕ 66.5	705KG	ϕ 30	ϕ 14.5	ϕ 73	690KG	ϕ 30	ϕ 14.5	ϕ 72.5	720KG	ϕ 30	ϕ 14.5	33	40	56			
20 Reverse	—	—	—	—																		
20 Normal	ϕ 65	540KG	ϕ 30	ϕ 14.5									700KG	ϕ 30	ϕ 14.5	—				—	—	—
19 Reverse																—				—	—	—
19 Normal																—				—	—	—
18 Reverse					—	—	—	—														

SPEC & PRICE LIST

MAVERICK 1705S 19inch REVERSE RIM

[2-piece]

SIZE	Price (JPY/1pc)			S-Lo Disk 5H-114.3								Lo Disk 5H-100 5H-112 5H-114.3 5H-120								Hi Disk 5H-114.3										
	SBC	HYPER METAL BLACK	GLAZE BLACK	Order Inset	Inset (Rim Depth) mm								Order Inset	Inset (Rim Depth) mm								Order Inset	Inset (Rim Depth) mm							
19×7.5J	¥94,000	¥88,000	¥84,000	50~42		47(43)	42(48)					43~35		42(41)	36(47)					27~19				27(40)	21(46)					
19×8.0J	¥95,000	¥89,000	¥85,000	55~37	53(44)	47(50)	41(56)					50~30	48(42)	42(48)	36(54)	30(60)				34~14				33(41)	27(47)	21(53)	15(59)			
19×8.5J	¥96,000	¥90,000	¥86,000	55~30	53(50)	47(56)	41(62)	35(68)				50~23	48(48)	42(54)	36(60)	30(66)	24(72)			40~7				39(41)	33(47)	27(53)	21(59)	15(65)	9(71)	
19×9.0J	¥97,000	¥91,000	¥87,000	55~22	53(56)	47(62)	41(68)	35(74)	29(80)	23(86)		50~15	48(54)	42(60)	36(66)	30(72)	24(78)	18(84)		46~-1	45(41)	39(47)	33(53)	27(59)	21(65)	15(71)	9(77)			
19×9.5J	¥98,000	¥92,000	¥88,000	55~22	53(63)	47(69)	41(75)	35(81)	29(87)	23(93)		50~15	48(61)	42(67)	36(73)	30(79)	24(85)	18(91)		46~-1	45(48)	39(54)	33(60)	27(66)	21(72)	15(78)	9(84)			
19×10.0J	¥99,000	¥93,000	¥89,000	55~28	53(69)	47(75)	41(81)	35(87)	29(93)			50~21	48(67)	42(73)	36(79)	30(85)	24(91)			46~-5	45(54)	39(60)	33(66)	27(72)	21(78)	15(84)	9(90)			
19×10.5J	¥100,000	¥94,000	¥90,000	55~24	53(75)	47(81)	41(87)	35(93)	29(99)			50~17	48(73)	42(79)	36(85)	30(91)	24(97)	18(103)		46~-1	45(60)	39(66)	33(72)	27(78)	21(84)	15(90)	9(96)			

NOTE: FOR OUTER RIM DEPTHS OF 45mm OR LESS, THE TOP SURFACE OF THE Disk PROTRUDES FROM THE EDGE OF THE RIM FLANGE.
 (When the outer rim depth is 45mm, 1.0mm protrudes.)

■ DISK FINISH: SBC, HMB (Hyper Metal Black), Glaze Black

■ COMPONENT PARTS : CENTER CAP (Selectable from 2 types of Hi type and 6 types of Lo type), AIR VALVE

■ RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

※ SAME PRICES ON YOUR CUSTOM ORDER.

※ The bolt hole diameter of all specs of MAVERICK 1705S are φ14.5. Hub collar ring is recommended when using M12 bolts and nuts.

SIZE	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)		
	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB φ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi
21 Normal	—	—	—	—	φ66.5	705KG	φ30	φ14.5	φ73	690KG	φ30	φ14.5	φ72.5	720KG	φ30	φ14.5	33	40	56
20 Reverse	—	—	—	—															
20 Normal	—	—	—	—															
19 Reverse	φ65	540KG	φ30	φ14.5															
19 Normal																			
18 Reverse					—	—	—	—											

SPEC & PRICE LIST

MAVERICK 1705S 19inch NORMAL RIM

[2-piece]

SIZE	Price (JPY/1pc)			S-Lo Disk 5H-114.3						Lo Disk 5H-100 5H-112 5H-114.3							
	SBC	HYPER METAL BLACK	GLAZE BLACK	Order Inset	Inset (Rim Depth) mm					Order Inset	Inset (Rim Depth) mm						
19×8.0J	¥95,000	¥89,000	¥85,000	41~23			38(58)	32(64)	26(70)		34~16			33(56)	27(62)	21(68)	
19×8.5J	¥96,000	¥90,000	¥86,000	47~16		44(58)	38(64)	32(70)	26(76)		40~9		39(56)	33(62)	27(68)	21(74)	15(80)
19×9.0J	¥97,000	¥91,000	¥87,000	53~23	50(59)	44(65)	38(71)	32(77)	26(83)		46~16	45(57)	39(63)	33(69)	27(75)	21(81)	
19×9.5J	¥98,000	¥92,000	¥88,000	53~17	50(65)	44(71)	38(77)	32(83)	26(89)	20(95)	50~10	45(63)	39(69)	33(75)	27(81)	21(87)	15(93)
19×10.0J	¥99,000	¥93,000	¥89,000	53~24	50(72)	44(78)	38(84)	32(90)	26(96)		50~17	45(70)	39(76)	33(82)	27(88)	21(94)	
19×10.5J	¥100,000	¥94,000	¥90,000	53~23	50(78)	44(84)	38(90)	32(96)	26(102)		50~16	45(76)	39(82)	33(88)	27(94)	21(100)	

* There is no protrusion of the top surface of the disk from the edge of the rim flange on all sizes.

■ DISK FINISH: SBC, HMB (Hyper Metal Black), Glaze Black

■ COMPONENT PARTS : CENTER CAP (Selectable from 2 types of Hi type and 6 types of Lo type), AIR VALVE

■ RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

※ SAME PRICES ON YOUR CUSTOM ORDER.

※ The bolt hole diameter of all specs of MAVERICK 1705S are ϕ 14.5. Hub collar ring is recommended when using M12 bolts and nuts.

SIZE	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)					
	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi			
21 Normal	—	—	—	—	ϕ 66.5	705KG	ϕ 30	ϕ 14.5	ϕ 73	690KG	ϕ 30	ϕ 14.5	ϕ 72.5	720KG	ϕ 30	ϕ 14.5	33	40	56			
20 Reverse	—	—	—	—																		
20 Normal	ϕ 65	540KG	ϕ 30	ϕ 14.5									700KG	ϕ 30	ϕ 14.5	—				—	—	—
19 Reverse																—				—	—	—
19 Normal																—				—	—	—
18 Reverse					—	—	—	—														

SPEC & PRICE LIST

MAVERICK 1705S 18inch REVERSE RIM

[2-piece]

SIZE	Price (JPY/1pc)			S-Lo Disk 5H-114.3						Lo Disk 5H-100 5H-112 5H-114.3							
	SBC	HYPER METAL BLACK	GLAZE BLACK	Order Inset	Inset (Rim Depth) mm					Order Inset	Inset (Rim Depth) mm						
18×7.5J	¥88,000	¥82,000	¥78,000	50~34		47(43)	41(49)	35(55)			43~27		42(41)	36(47)	30(53)		
18×8.0J	¥89,000	¥83,000	¥79,000	55~29	53(44)	47(50)	41(56)	35(62)	29(68)		50~22	48(42)	42(48)	36(54)	30(60)	24(66)	
18×8.5J	¥90,000	¥84,000	¥80,000	55~22	53(50)	47(56)	41(62)	35(68)	29(74)	23(80)	50~15	48(48)	42(54)	36(60)	30(66)	24(72)	18(78)
18×9.0J	¥91,000	¥85,000	¥81,000	55~22	53(56)	47(62)	41(68)	35(74)	29(80)	23(86)	50~15	48(54)	42(60)	36(66)	30(72)	24(78)	18(84)
18×9.5J	¥92,000	¥86,000	¥82,000	55~22	53(63)	47(69)	41(75)	35(81)	29(87)	23(93)	50~15	48(61)	42(67)	36(73)	30(79)	24(85)	18(91)
18×10.0J	¥93,000	¥87,000	¥83,000	55~28	53(69)	47(75)	41(81)	35(87)	29(93)		50~21	48(67)	42(73)	36(79)	30(85)	24(91)	

NOTE: FOR OUTER RIM DEPTHS OF 45mm OR LESS, THE TOP SURFACE OF THE Disk PROTRUDES FROM THE EDGE OF THE RIM FLANGE.
(When the outer rim depth is 45mm, 1.0mm protrudes.)

■ DISK FINISH: SBC, HMB (Hyper Metal Black), Glaze Black

■ COMPONENT PARTS : CENTER CAP (Selectable from 2 types of Hi type and 6 types of Lo type), AIR VALVE

■ RIM DEPTH: THE DISTANCE BETWEEN THE OUTER EDGE OF DISK AND OUTER RIM FLANGE.

※ SAME PRICES ON YOUR CUSTOM ORDER.

※ The bolt hole diameter of all specs of MAVERICK 1705S are ϕ 14.5. Hub collar ring is recommended when using M12 bolts and nuts.

SIZE	5H/100				5H/112				5H/114.3				5H/120				Height of hub clearance (mm)																		
	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	HUB ϕ	VIA	LUG HOLE DIA	BOLT HOLE DIA	S-Lo	Lo	Hi																
21 Normal	—	—	—	—	ϕ 66.5	705KG	ϕ 30	ϕ 14.5	ϕ 73	690KG	ϕ 30	ϕ 14.5	ϕ 72.5	720KG	ϕ 30	ϕ 14.5	33	40	56																
20 Reverse	—	—	—	—									—	—	—	—				—	—	—	—	—	—	—									
20 Normal	ϕ 65	540KG	ϕ 30	ϕ 14.5									700KG	ϕ 30	ϕ 14.5	ϕ 73				690KG	ϕ 30	ϕ 14.5	—	—	—	—	—	—	—						
19 Reverse																							—	—	—	—	—	—	—	—	—	—	—	—	—
19 Normal																							—	—	—	—	—	—	—	—	—	—	—	—	—
18 Reverse	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—																	